

CHOOSE BEECHWORTH WINDOWS AND YOU CHOOSE TO HAVE THE BEST EXPERIENCE

CONFIDENCE

Performance fiberglass windows built on the foundation of a 125-year history in building materials innovation.

SIMPLICITY

The right selection, the right fit, and great contractors, for the best experience.

PRIDE OF OWNERSHIP

For the customer who wants rich wood interiors without compromising quality, covered by an industry leading warranty.

The Beechworth picture window can stand alone or connect to another functioning window to meet a desired visual effect. Add grilles and patterns for depth or keep it simple and enjoy the view.



Reliable

→ Sliding windows stay strong in all sizes

Complementary

→ Combine with other windows for variation

Comfortable

→ All windows are NFRC approved



15x stronger than vinyl substrate

2x stronger than aluminum substrate

12x less movement than vinyl substrate

5x less movement than aluminum substrate

STRENGTH

- Holds its shape during transport
- Resists damage from impact
- Resists dipping, delaminating, sagging
- Looks great over time

STABILITY

- Lower movement means less expansion
- Less expansion is less stress on the window
- Less stress on window is better performance
- Longer performance indicates better value



These figures are for the full frame picture window.

<p>U-FACTOR Typically between .15 and 1.2, U-Factor figures indicate how well a window can prevent wanted heat from escaping. This takes into account multiple variants that could affect the window's ability to keep heat in: conduction, convection and emmissivity of the glass.</p>	Standard	Advanced	Max
	.27	.26	.22
	Standard	Advanced	Max
	.36	.24	.23
<p>VISIBLE TRANSMITTENCE Between 0-1, a higher VT indicates greater potential for daylighting, or the amount of light that will come through the window. The Standard glass package allows more light, because it has fewer low-e coatings, for example.</p>	Standard	Advanced	Max
	.63	.57	.51
	Standard	Advanced	Max
	60	61	49
<p>CONDENSATION RESISTANCE Optional rating between 10-100. Higher figures indicates better resistance to condensation.</p>	Standard	Advanced	Max
	60	61	49
	Standard	Advanced	Max
	60	61	49

*Performance statistics are based on internal testing at the Beechworth R&D facility, and publically available 3rd party information.